

AVALANCHE - RT66

PREMIUM ORGANIC ASPHALT RELEASE AGENT

Features & Benefits

- Organic
- Safer than Table Salt
- 100% Biodegradable & Non Toxic
- Delivers a Super Slick Release
- Non-Hazardous
- Non-Flammable
- Non DOT Regulated
- Effective on all Polymer Type Asphalt Mixes
- Can be used in Automatic Spray Systems
- Does not Evaporate
- Outstanding Solvent Properties
- Easy Cleanup of Equipment
- Does not contain Petroleum
 Distillates
- Safe for Animals and the Environment

PRODUCTSIZES

5 Gallon Pail (20 L) 55 Gallon Drum (208 L) 275 Gallon Tote (1,045 L)



P.O. BOX 23162 1706 - 4st SW, Calgary, AB T2S 381 WWW.KCPE.CA * 866.637.5474

Description

AVALANCHE-RT66 is a ready-to-use asphalt release agent formulated for coating asphalt truck beds, tooling equipment, drag chains, and all moving parts in hot plants that produce asphalt. AVALANCHE-RT66 is a maximum slip agent that lubricates all moving parts, protect, conditions and provides corrosion protection for your equipment. AVALANCHE-RT66 will not be washed off by rain water, thus giving you continuous protection against rusting. AVALANCHE-RT66 is user and environment friendly and will not harm environmental reserves or wildlife.

AVALANCHE-RT66 exceeds all Federal, State and Provincial VOC requirements as it is made from organic plan matter. Therefore it is EPA compliant and Non DOT Regulated.

Directions for Use

AVALANCHE-RT66 is a ready-to-use asphalt release agent to be used in truck beds or as an anti-stick agent to prevent asphalt and tar from adhering to equipment and moving parts. AVALANCHE-RT66 can be applied with a hand sprayer or pneumatic spray system. For easy release of asphalt from truck beds, apply approximately 12 - 16 oz. AVALANCHE-RT66 can be applied minutes or hours before loading or commencing operations.

Technical Specifications

Appearance: Thin Amber Liquid Concentrate PH@ Concentrate: 6.0 - 7.0 Specific Gravity: 0.88 Boiling Point: >400 F Flash Point: 280 - 300 F Solubility in Water: Non-Soluble VOC: Compliant