

**DIRECTIONS**

:

Dilute 1 part RIGHT OFF to 3 parts water in a 5 gallon bucket and apply to surfaces to be cleaned. Allow 2-3 minutes contact time and then brush all areas thoroughly. Apply again, let stand and brush again to remove heavier build-up. When cleaning greasy areas allow contact time and brush as you would for cement removal. Rinse thoroughly. Heavy build-up on neglected or un-assigned trucks can be eliminated by washing in the usual manner then applying truck cleaner again on build-up only and allow to react. Brush affected areas the following day and use a putty knife or scraper where necessary, repeat the process daily for several days until all build-up is removed. RIGHT OFF should not be used on the cabs of trucks as the regular truck cleaner, but may be used on occasion to remove cement dust and splatter. Rinse completely.

REMOVES & PROTECTS FROM:

- Rust • Grease • Oil • Hydraulic Fluids • Concrete • Dirt

RIGHT OFF can be used as a daily truck wash to remove built-up concrete without any neutralization. Using RIGHT OFF as a daily wash will eliminate all rusting issues on your equipment. The phosphoric action removes old rust and oxides, and conditions the metal so that no new rust is created during the cleaning process. RIGHT OFF doubles as an excellent grease and road film remover. Plus, RIGHT OFF is so safe, it can be used on any surface, including glass, aluminum, chrome, rubber, plastic, or paint. RIGHT OFF also includes detergents for degreasing, corrosion inhibitors, optical brighteners, foaming agents, and water softeners.



Safety, Storage, Shelf Life: Always wear proper PPE when handling or working with any chemical. Do NOT apply any chemicals on sun baked surfaces. Product is guaranteed for one year in original container.

RIGHT OFF

TRUCK WASH

Prevents Rust and Eliminates Concrete Buildup

- REMOVES ALL TYPES OF GREASE, OIL, DIESEL AND HYDRAULIC FLUIDS • 100% PHOSPHORIC
- BLENDED NON-IONIC DETERGENT + POLAR SOLVENT



○ 2.5 Gal.

○ 5 Gal.

○ 55 Gal.

○ 275 Gal.

HEALTH HAZARD DATA, EFFECTS OF OVEREXPOSURE, FIRST AID:

Inhalation: No hazards expected. If symptoms occur, remove affected person to fresh air; if breathing has not returned to normal within a few minutes after exposure, get medical attention.

Skin: No hazards expected. If contact occurs, wash affected area with soap and water; remove and launder contaminated clothing before reuse; if irritation occurs, seek medical attention.

Eyes: Remove contact lenses. Immediately flush eyes for 15 minutes in clear running water while holding eyelids open; seek medical attention.

Ingestion: Drink two glasses of water followed by milk, milk of magnesia or other nonalcoholic liquids; DO NOT induce vomiting; seek medical attention.

Carcinogens: Product contains no known carcinogens.

NFPA Rating

0 = Non - Hazardous
1 = Slight Hazard
2 = Hazardous
3 = Extreme hazard
4 = Deadly

MADE IN ACCORDANCE
WITH ALL GOVERNMENT
REGULATIONS



D.O.T. Non-Regulated

In Case of Emergency, Contact: Chem-Tel 24hrs. (800) 255-3924



MADE IN CANADA
in association with
Power Kleen.



www.KCPE.CA (866) 637-5474